

# AMERICAN CORNERBEAD COMPANY

TO ORDER

PHONE: (704) 868-2277

FAX: (704) 868-2020



Furring channel, a galvanized hat-shaped multi-purpose framing component that is used on masonry walls and ceiling assemblies. Our 25 gauge is hemmed to provide safety and structural integrity.

PRODUCT	GAUGE	DIMENSIONS	LENGTH	PIECES PER BUNDLE	FT PER BUNDLE	BUNDLES PER PALLET
Furring Channel	25	7/8"	10'	10	100	25
Furring Channel	25	7/8"	12'	10	120	25
Furring Channel	20	7/8"	10'	10	100	25
Furring Channel	20	7/8"	12'	10	120	25
Furring Channel	18	7/8"	10'	10	100	25
Furring Channel	18	7/8"	12'	10	120	25



Resilient Channel (RC2) reduces sound waves and transmission by suspending drywall from the wall and ceiling.

PRODUCT	GAUGE	DIMENSIONS	LENGTH	PIECES PER BUNDLE	FT PER BUNDLE	BUNDLES PER PALLET
RISILIENT CHANNEL 2 (RC2)	25	1/4 X 1/4	12'	10	120	50



093 Zinc Control Joint is used to provide a mechanism for movement to accommodate expansion and minor thermal movement. It comes pre-taped to provide a clean finish.

PRODUCT	DIMENSIONS	LENGTH	PIECES PER CARTON	FT PER CARTON	CARTONS PER PALLET	FT PER PALLET
093 Zinc Control Joint	7/8 x 7/8	10'	25	250	20	5000

# AMERICAN CORNERBEAD COMPANY

TO ORDER

PHONE: (704) 868-2277

FAX: (704) 868-2020



Z-Furring is an ideal product for furring out the interior walls on an existing masonry or new concrete-masonry walls.

**SPECIAL ORDERS ONLY. CALL FOR DETAILS**

PRODUCT	GAUGE	DIMENSIONS	LENGTH	PIECES PER BUNDLE	FT PER BUNDLE	BUNDLES PER PALLET
Z-Furring Channel	25	1"	10'	10	100	25
Z-Furring Channel	25	1-1/2"	10'	10	100	25
Z-Furring Channel	25	2"	10'	10	100	25
Z-Furring Channel	25	1"	12'	10	120	25
Z-Furring Channel	25	1-1/2"	12'	10	120	25
Z-Furring Channel	25	2"	12'	10	120	25
Z-Furring Channel	20	1"	10'	10	100	25
Z-Furring Channel	20	1-1/2"	10'	10	100	25
Z-Furring Channel	20	2"	10'	10	100	25
Z-Furring Channel	20	3"	10'	10	100	25
Z-Furring Channel	20	1"	12'	10	120	25
Z-Furring Channel	20	1-1/2"	12'	10	120	25
Z-Furring Channel	20	2"	12'	10	120	25
Z-Furring Channel	20	3"	12'	10	120	25



Multi-purpose 90 degree L-Shaped angle iron with 2 legs. The legs of the "L" can be equal or unequal in length. Steel angles are used for various purposes in a number of industries.

PRODUCT	GAUGE	DIMENSIONS	LENGTH	PIECES PER BUNDLE	FT PER BUNDLE	BUNDLES PER PALLET
Angle	25	1 1/2 " x 1 1/2 "	10'	10	100	25
Angle	25	2 " x 2 "	10'	10	100	25
Angle	20	1 1/2 " x 1 1/2 "	10'	10	100	25
Angle	20	2 " x 2 "	10'	10	100	25
Angle	20	3 " x 3 "	10'	10	100	25
Angle	18	1 1/2 " x 1 1/2 "	10'	10	100	25
Angle	18	2 " x 2 "	10'	10	100	25
Angle	18	3 " x 3 "	10'	10	100	25
Angle	16	1 1/2 " x 1 1/2 "	10'	10	100	25
Angle	16	2 " x 2 "	10'	10	100	25


# AMERICAN CORNERBEAD COMPANY

TO ORDER

PHONE: (704) 868-2277

FAX: (704) 868-2020

Angle	16	3 " x 3 "	10 '	10	100	25
Angle	14	1 1/2 " x 1 1/2 "	10 '	10	100	25
Angle	14	2 " x 2 "	10 '	10	100	25



Commonly used in wall bridging and lateral bracing. Flat strap is a tension element used to transfer loads between diagonally located strap tracks.

PRODUCT	GAUGE	DIMENSIONS	LENGTH	PIECES PER BUNDLE	FT PER BUNDLE	BUNDLES PER PALLET
Flat Strapping	20	3 "	10 '	10	100	10
Flat Strapping	20	4 "	10 '	10	100	10
Flat Strapping	20	6 "	10 '	10	100	10 & 20
Flat Strapping	18	2 "	10 '	10	100	10
Flat Strapping	18	3 "	10 '	10	100	10
Flat Strapping	18	4 "	10 '	10	100	10
Flat Strapping	18	6 "	10 '	10	100	10
Flat Strapping	16	2 "	10 '	10	100	10
Flat Strapping	16	3 "	10 '	10	100	10
Flat Strapping	16	4 "	10 '	10	100	10
Flat Strapping	14	1 1/2 "	10 '	10	100	10
Flat Strapping	14	2 "	10 '	10	100	10
Flat Strapping	14	3 "	10 '	10	100	10